

Bell Schedules (Core v3.X)

Last Modified on 03/11/2024 8:45 am CD7

Tool Search: Ed-Fi

This entity represents the schedule of class period meeting times.

Object Triggering Logic

This table describes logic for triggering syncing of this object.

Action	Trigger
Post	 When a Period Schedule is created and saved. A separate record will be sent for each Period Schedule/Period Name/Schedule Structure ID combination created. Do not send records if the Calendar Exclude check box is checked. Do not send a record if the School Exclude checkbox is checked.
Put	 When any field not part of the Natural Key is changed: Period Name If the Period Schedule is added or removed to a day on the Days tab. If a Grade Level that is mapped to an Ed-Fi code is added/removed from the Schedule Structure. If the Instructional Day checkbox is added/removed.
Delete/Post	When any field part of the natural key is changed. • Period Schedule Name
Delete	When all Periods in a Period Schedule are deleted or the Period Schedule is deleted.

School Exclude, Calendar Exclude, Resource Toggle and Resync Logic

This table describes the School Exclude, Calendar Exclude, Resource Toggle and Resync logic of this object.

Action	Trigger
None	If a resource is toggled to 'OFF' after data has sent, all sent data will remain in the ODS but no new data will send.
Delete	If a resource is toggled to 'OFF" after data has sent and an action is performed that would trigger a delete, that data will remain in the ODS until a resync is done.
Resync	If a record is in the Ed-Fi Identity Mapping table and not in the ODS, it will be deleted from the Ed-Fi Identity Mapping table.
Resync	If a record is in the ODS and it does not have a matching record in Campus or the Ed-Fi Identity Mapping table, it will be deleted from the ODS.
Resync	If a mapping is changed in Resource Preferences, a resync will need to be done to reflect the changes.

Natural Key Changes, Cascading Updates, and Deletes Logic

This table describes the Natural Key Changes/Cascading Updates and Deletes logic of this object.



Action	Trigger
Delete/Post	If any of the following changes in the Schools resource: • If the School Number/Ed-Fi School Number changes, a delete/post will occur with the cascading deletes from the School ID change triggers.
Delete/Post	If Period Schedule Name or Period Name Changes.

Scope Year Logic

This table describes scope year logic of this object.

Logic

Period Schedules will only send for the school year to which they are aligned.

• Data will only send for years that have valid configuration.

Event Queue Detail

This table describes the Event Queue Detail of this object.

Campus Table	Ed-Fi Action	Fields
periodschedule	Post/Put/Delete	The primary tables used for sending data for this resource.
period	Put	Class Periods Reference
days	Put	Dates
gradelevel	Put	Grade levels

Object Data Elements

This table describes data elements sent within the Bell Schedules resource.

Data Element Label	Business Requirement	Business Rules	M, C or O	Data Source GUI Path	Database Field
id	Id	The unique identifier of the resource.	М		



Data Element Label	Business Requirement	Business Rules	M, C or O	Data Source GUI Path	Database Field
bellScheduleName	Name or title of the Bell Schedule.	Report the Period Schedule Name + Schedule Structure ID 1. Report a space between each value.	М	System Administration> Calendar> Calendar> Periods System Administration> Calendar> Calendar> Calendar> Schedule Structure	periodschedule.name + schedulestructure.structur
classPeriods	An unordered collection of bellScheduleClassPeriods. The class periods that compose this BellSchedule.	Reports the Class Period reference for all periods in the period schedule. 1. See array section below.	М		
schoolReference	A reference to the related School resource.	Reports the fields that are part of the Natural Key for the Schools resource.	М		
alternateDayName	An alternate name for the day (e.g., Red, Blue).	Report the Period Schedule Name.	0	System Administration> Calendar> Calendar> Periods	periodschedule.name
dates	An unordered collection of bellScheduleDates. The dates for which the BellSchedule applies.	Reports all of the dates the period schedule is aligned to 1. See array section below.	0		



Data Element Label	Business Requirement	Business Rules	M, C or O	Data Source GUI Path	Database Field
gradeLevels	An unordered collection of bellScheduleGradeLevels. The grade levels the particular BellSchedule applies to.	Reports all of the grade levels in the schedule structure the period schedule is aligned to. 1. See array section below.	0		
etag					

Arrays

▶ Click here to expand...

Type/Descriptors

▶ Click here to expand...