

Custom Attribute/Dictionary


Last Modified on 03/06/2026 3:00 pm CST

[Create a Custom Field](#) | [Sorting Logic](#)

Tool Search: Custom Attribute/Dictionary

The Custom Attribute/Dictionary is used to view and create new custom fields for the user interface.

Custom attributes are custom interface fields that can be created at the district/state level for storing localized information not otherwise tracked by an existing Campus field. Custom attributes can be added to certain core tools or to any custom tools created via [Custom Tool Setup](#).



The Custom Attribute tool creates user interface fields that are stored as database attributes within the *campusAttribute* table.

Information to be contained in a custom field should NOT already have a designated area in the Campus product. Campus recommends conducting a thorough review of existing Campus functionality and schema and/or contacting a Campus Support representative before creating custom fields.

Custom Attributes vs. Core Attribute/Dictionary

The Custom Attribute tool allows a district/state to view, create, and manage its own localized custom fields.

The purpose of the [Core Attribute Dictionary](#) tool is to view all core elements within the application, organized by state and district. Locally created elements can be created, viewed, and modified in the Custom Attribute tools. Locally created elements are only viewable within the Custom Attribute tool and do not display within the Core Attribute/Dictionary tool.

Refer to the [Custom Data and Links Tool Rights](#) article for details on tool rights for this and related tools.


Create a Custom Field

Note the following:

- Custom fields added to core tools appear in the District Defined Elements editor for that tool.
- If the custom field resides on a custom tool, the tool must be created before proceeding with the following steps.
- Any custom attribute that contains the word "time" cannot be queried in Ad hoc tools if it is not an actual time field.

A custom field contains data not otherwise tracked in Campus. The field's details, format, size, and associated codes/values are configured through this tool.

1. Click the **New** icon. The Campus Attribute Detail editor will appear below.



New Custom - Attribute Detail

Display Name: (Required)
 Participating in Program

Field Name: (Required)
 ProgPart

Data Type: (Required)
 dropList

Screen Location: (Required)
 Enrollment

Max Size:
 Must be empty or between 1 and 255
 0

Sequence:
 Must be empty or between 0 and 255
 0

Default Selection:
 None

Hide:

Required:

Hide Portal:

Copies Forward:

Comments:

2. Enter the **Display Name** of the field you would like to add. This is the name that appears in the UI for the field.

3. Enter the **Field Name**. This is the name used to identify the field in the database.
4. Select the **Data Type**. This determines the type of field presented to users. Refer to the table below for additional information.
 - ▶ [Click here to expand...](#)

Data Type	Details
textBox	<p>Creates a text box.</p> <p>Users are allowed to enter up to 255 alphanumeric and special characters.</p>
drop-down list	<p>Creates a dropdown list.</p> <p>Limited to 15 alphanumeric characters.</p>
dateField	<p>Creates a date field.</p> <p>Users must enter the date in MM/DD/YYYY, MM-DD-YY or MMDDYY format.</p>
numberField	<p>Creates a number field.</p> <p>Only numeric characters (no decimals) are allowed. Max default value is 10.</p>
floatField	<p>Creates a float field.</p> <p>Only numeric characters are allowed with one decimal point.</p> <p>The max default value is 10. The value can be without a decimal point. If the default value has a decimal, only 2 numbers to the right of the decimal are allowed.</p>
timeField	<p>Creates a time field.</p> <p>Users must enter values in HH:MM AM/PM or HH:MM military time. Values should include a semicolon.</p>
ssnField	<p>Creates a field for entering a Social Security Number.</p> <p>Users must enter a number pattern of XXX-XX-XXXX where X = a numeric value between 0-9. Dashes should be included when entering Social Security Numbers. 11 characters total (this includes the dashes between numbers).</p>
phoneField	<p>Creates a field for entering phone numbers.</p> <p>Users should enter phone values in (999)999-9999 or (999)999-9999x9999 format where:</p> <ul style="list-style-type: none"> ◦ 9 = a numeric value between 0-9 ◦ x = the delimiter for entering an extension number

Data Type	Details
emailField	<p>Creates a field for entering an email address.</p> <p>Users must enter email addresses in XXXXX@XXX.XXX where:</p> <ul style="list-style-type: none"> ◦ X = any alphanumeric or special characters ◦ Users may enter multiple periods ◦ Number of total characters does not surpass 100 ◦ @ is required
moneyField	<p>Creates a field for entering a monetary value.</p> <p>Users must enter a value between 0-9. One decimal point is allowed but only two numbers right of the decimal point are allowed. Values entered can contain the \$ special character but is not required.</p>
checkBox	Creates a checkbox.

5. Select the **Screen Location**. This is where users will interact with this field.
6. Enter any additional information. Refer to the table below for more information on these fields.

Fields	Description
Max Size	The maximum number of characters allowed for entry in the field.
Sequence	<p>The order of the field within the tool.</p> <p>For example, Field A has a seq of 1 and Field B has a Seq of 2. Field 1 will be listed first followed by Field 2.</p> <p>If no sequence is indicated, fields display in numeric or alphabetic order.</p>
Default Value/Text	<p>The default value that auto-populates the field when a new record is created.</p> <div style="background-color: #fff9c4; padding: 5px; border: 1px solid #ccc;"> <p>Note that default values are NOT saved in the database tables.</p> </div>
Hide	If marked, this custom field will not display within the UI for any users. This is useful for hiding a previously active field from being used.
Required	If marked, this checkbox indicates that the field must be filled out (or checked) for the user to save a record in the custom tool. The field name appears in red (instead of black) and is followed by an asterisk (*) to indicate it is required.
Hide Portal	<p>If marked, this checkbox indicates the custom field will not be displayed in the Student or Parent Portal.</p> <p>This field does not apply or appear to state-level users.</p>

Fields	Description
Copies Forward	<p>When marked, the data associated with the attribute is copied forward into the calendar for the next school year.</p> <p>This option applies to things that are cloned or rolled forward from year to year. For example, calendars are carried over from one year to the next, courses are carried forward, and enrollments are carried forward.</p> <p>People are not tied to a calendar; therefore, attributes associated with people are not copied forward, even when this checkbox is marked.</p> <p style="background-color: #fff9c4; padding: 5px;">This option is not available for data fields assigned to a custom tab.</p>
Comments	Any comments related to the custom field. These comments do not display for users interacting with the field.

- If the field you added requires a value, such as a dropdown, you need to define the values it can display. Click **Add new** to begin adding these values.
- Enter the necessary information for the value and save each value by clicking **Done**. Repeat this process for all values that should populate your new field.

Participating in Program - Attribute Dictionary Detail

Code (Required)	Name (Required)	Sequence	Value	Standard Code	Active	
<input type="text"/>	<input type="text"/>					
3	<input type="text"/>	0	<input type="text"/>	<input type="text"/>	<input checked="" type="checkbox"/>	<input type="button" value="Done"/> <input type="button" value="Cancel"/>
2	Title1	0			true	<input type="button" value="Edit"/> <input type="button" value="Remove"/>
1	LEP	0			true	<input type="button" value="Edit"/> <input type="button" value="Remove"/>

« ‹ 1 › » 1 - 2 of 2 items

- Enter all required field values, and then click **Save** once you are finished. Your custom field is now available in the designated tool, and its values are available within it.

Custom Tools and Custom Attributes

[Custom Tool Setup](#) allows you to create custom tools for tracking local or state-level information. You can also use this tool to embed hyperlinks to appear as a tool within the Infinite Campus navigation and have these links open in a new tab or within the workspace. When a custom tool is created, it still requires custom attributes to be defined, as these are the custom fields and field values that will populate the custom tool. The easiest way to think of this is:

- The custom tool is created via Custom Tool Setup.

2. Once created, you need to use the Custom Attribute/Dictionary to create the fields and field values that will appear in this tool.
3. Once the custom tool has been created and fields added, district users can begin entering data and creating new records in this tool.

For a step-by-step walkthrough of this process, please see the [Custom Tool Setup](#) article.

Custom Fields (Database-Only)

The following fields of the *campusAttribute* table relate to creating/modifying custom fields. These fields are only available in the database; they do not appear in the user interface. This is not a complete list of database fields.

Database Column	Description
attributeID	Internal database identifier used as a reference in other tables.
coreLock	<p style="background-color: #fff9c4; padding: 5px;">This column no longer impacts the function of an attribute.</p> <p>Controls whether a user may modify the settings of an attribute field through the user interface.</p> <p>If set to a value of "1" (a true value), the attribute field settings is locked and system administrators are not be able to modify the settings on the Custom Attribute or Attribute/Dictionary tools.</p>
custom	<p>Indicates whether the attribute was created by a Campus user or is a core field.</p> <p>If set to a value of "1" (value of "true"), the custom attribute field was created within Campus by a registered user.</p>
dated	<p>Retains historical information of custom fields by setting the date on each entry and creating a new entry for each change.</p> <p>0 or Null = Any change results in the current row being updated, but with no date set.</p>
lock	<p>Controls whether a user may add/change/delete dictionary values (codes) for the custom attributes within the user interface.</p> <p>If set to a value of "1" (a true value), the dictionary values (codes) of a custom attribute are locked and system administrators are not be able to modify the dictionary values on the Custom Attribute tool.</p>

Database Column	Description
statusData	<p>Controls whether the values of the custom field are stored in one of the custom tables named as “custom” followed by the object (<i>e.g., customStudent</i>).</p> <p>If set to a value of “1” (a true value), custom field values are stored in a custom table. Otherwise, values are stored in the table and column specified by object and element, respectively.</p> <p>This flag and the stateTable flag are mutually exclusive. Only one should be set at a time.</p>
stateTable	<p>Controls whether or not values of the custom field are stored in a state-specific table named as the custom object followed by the state abbreviation appended (<i>e.g., EnrollmentME</i>).</p> <p>This flag and the statusData flag are mutually exclusive. Only one should be set at a time.</p>

Custom Dropdown List Fields

The following fields are displayed in the Dictionary Detail editor when creating codes/values associated with a custom dropdown list field in the user interface. This data is stored in the *campusDictionary* table.

Field	Description	Database Location
Code	<p>An abbreviated version of the value that displays directly before the value entered in the Name field when displayed for selection within the custom field.</p> <p>For example, if the value in the Code field is <i>1P</i> and the value in the Name field is <i>First Priority</i>, the dropdown item available for selection from the custom field displays as <i>1P: First Priority</i>.</p>	CampusDictionary. code
Name	<p>Text descriptor of the code value as it should display in the custom field dropdown list. This directly follows the value entered in the Code field when displayed for selection within the custom field.</p> <p>For example, if the value in the Code field is <i>1P</i> and the value in the Name field is <i>First Priority</i>, the dropdown item available for selection from the custom field displays as <i>1P: First Priority</i>.</p>	CampusDictionary. name
Seq	The order of the custom field on the tab, as related to the other fields on the tab.	CampusDictionary. seq

Field	Description	Database Location
Value	Used to store additional, localized data related to the value (mapping a local value to state values) and/or for state-reporting purposes. This text is not displayed to end users as part of the visible dropdown list value.	CampusDictionary.value
StandardCode	Used for SIF naming purposes. This text is not displayed to end users as part of the visible dropdown list value.	CampusDictionary.standardCode
Active	If marked, the checkbox indicates the value should be actively available for selection from the dropdown custom field to which it is assigned. If this checkbox is not marked, the dictionary item does not display in the dropdown field.	CampusDictionary.active
Database-Only Fields		
The following fields of the <i>campusDictionary</i> table relate to creating codes/values for custom dropdown list fields. These fields are only available in the database; they do not appear in the user interface.		
dictionaryID	Internal database identifier that can be referenced by other tables.	
attributeID	Internal database identifier - foreign key from the <i>campusAttribute</i> table.	

When the total number of dictionary items is greater than or equal to 50, the dropdown list on the tool becomes an auto-search field, allowing the user to type the first few letters of the item and the available choices filter to those matching the entered text.

Sorting Logic

Depending on the type of Data Type selected for a Custom Attribute, the attributes assigned to that data type sort differently.

Data Type	Sorting Hierarchy
Single Screen Editor	<ol style="list-style-type: none"> 1. Sequence 2. Display Name
Table Editor	<ol style="list-style-type: none"> 1. Sequence 2. Display Name
Dropdown Lists	<ol style="list-style-type: none"> 1. Sequence 2. Code

Data Type	Sorting Hierarchy
List Editor	<ol style="list-style-type: none"> 1. Sequence 2. Display Name

When these custom tabs/attributes are available on the Campus Portal, the following hierarchy applies.

Data Type	Sorting Hierarchy
Single Screen Editor	<ol style="list-style-type: none"> 1. Sequence 2. Display Name
List Editor	<ol style="list-style-type: none"> 1. Sequence 2. Display Name
Table Editor	<ol style="list-style-type: none"> 1. Date and Time Descending 2. Sequence 3. Display Name