

Register the SIF Agent

Last Modified on 01/20/2026 9:45 am CST

This article is part of an ordered [SIF Configuration process](#) and applies to both methods of configuration ([Horizontal](#) and [Vertical](#)).

Before beginning, please consider this setup step in relation to the ordered setup steps of the [SIF Configuration](#) process:

- [Setup School SIF Codes](#)
- [Setup SIF Grade Levels](#)
- [Setup SIF Zone](#)
- [Setup SIF Agent](#)
- [Setup SIF Data Access Rights](#)
- [Register Agent](#)
- [Request Data Sync](#)

This article contains basic information and instructions for configuring communication between a Campus and SIF application. The basic process of configuring SIF communication follows these steps:

Only an advanced technical user should attempt to set up SIF communication.

Agents ☆

System Settings > Data Interchange Settings > Agents

Agent List	
Name	<script>alert()</script>a
Agent	Erin
MN028101Campus	
MN028101CampusRouter	

Agent Info
Campus Agent is not running on this server (It may be running on another in the cluster).
Name: MN028101Campus Queue: 0 Use Gzip On Send

Incoming Host
Header Field: IP Address:
Add DISAgentIncomingHost

Description
DIS/ZIS and SIS Agent

Registered Yes
Status Authorized to exchange data

Sleeping No
Selective Blocking(SMB) false
Connection Type Agent
Max Buffer 15000000
URL of zone to push to

Note: The Campus Agent is built-in to the system and are not configurable using this interface.

Agents

Registering SIF Agent

Before data can be exchanged, the SIF agent must send a registration message to the SIF

zone. This process is triggered through the buttons on the Agent Emulation Control panel of the SIF agent.

In some instances of [Horizontal Reporting](#), this step will not be necessary. When a SIF agent is set up in the external SIF application it can register with the Campus application using the Campus SIF Zone URL, and a registered and configured agent will appear on the Agents tool. If this scenario applies, continue to [Request Data Sync](#), or return to the [SIF Configuration](#) page.

Agents ☆

System Settings > Data Interchange Settings > Agents

New Save Delete View Queue Purge Queue View Log Purge Log

Agent List

- Name: <script>alert()</script>a
- AgentErin
- MN028101Campus**
- MN028101CampusRouter

Agent Info

Campus Agent is not running on this server (It may be running on another in the cluster)

Name: MN028101Campus **Queue:** 0 **Use Gzip On Send:**

Incoming Host

Header Field: **IP Address:**

Add DISAgentIncomingHost

Description: DIS/ZIS and SIS Agent

Registered: Yes **Sleeping:** No

Status: Authorized to exchange data **Selective Blocking(SMB):** false

Subscribe Mode: Push **Connection Type:** Agent **Max Buffer:** 15000000

XML Language: Infinite Campus **URL of zone to push to:**

Note: The Campus Agent is built-in to the system and are not configurable using this interface.

Agents Editor

1. On the SIF agent, verify the **Registered** field is set to "Yes."
2. Verify the SIF zone is displayed in the **Zone Name** field.
3. This step only applies to SIF agents with a **Subscribe Mode** value of "Push."

If using Push mode and no value appears in the **Outgoing Host Override** field, enter the externally accessible IP address of the SIF application. When registering a SIF agent operating in Push mode, the URL is sent to the external zone. It will be a generated value based on the URL currently used to browse the site.

4. Click the **Register** button on the Agent Emulation Control panel. A *SIF_Register* message will be sent to the SIF application, allowing it to identify the SIF agent acting on behalf of the Campus application. A new window should open.
5. Verify the new window displays an XML response from the SIF application. This is the *SIF_Ackmessage* acknowledging a successful connection.

If registering for SIF 2.0r1, the response message will contain a *SIF_AgentACL*, or data access rights for data objects that the Campus agent has been pre-approved to publish / the objects

the SIF agent expects to receive. This is a SIF 2.0r1 feature, so previous SIF versions will not contain this data.

6. Click the **Save** button of the Campus action bar to save the newly registered agent.

Data Provide and Subscribe

This section applies to [Vertical Reporting](#) scenarios only.

1. Select the agent and re-open it.
2. *For SIF versions 2.0r1 and later:* Click the **Provision (2.0r1)** button. This sends a *SIF_Provision* message to the external SIF zone to let it know which objects the Campus agent will be publishing (and any to which the Campus agent should subscribe/receive updates from the SIF application)
OR,
For SIF versions prior to 2.0r1: first click the **Provide** button, then the **Subscribe** button.
3. Click **Save**.

From this point forward, data exchange is possible.

To continue SIF setup, proceed to [Request Data Sync](#), or return to the [SIF Configuration page](#).
